



The industry's first dual-phone wireless tabletop conferencing system. MAXAttach Wireless provides expanded wireless coverage for medium-sized conference rooms, delivering clear, full-duplex audio through two complete phone units – all with no cables in the way.

HDConference Audio

- + Distributed Echo Cancellation® and noise cancellation along with full-duplex performance and automatic level controls guarantees your conference calls to be natural with unmatched audio clarity without any distractions

Acoustic Intelligence

- + First-mic priority intelligently activates only the microphone closest to the person speaking, preventing the amplification of ambient noise and room reflections

360-degree Coverage

- + Three built-in microphones create array with 360-degree audio pickup within 12 feet of each conference phone. Large loudspeaker for rich, clear conferencing and audio playback

Expandable Design

- + Daisy-chainable design can expand up to two complete phones wirelessly to cover medium-size rooms. Full conference phone expandability allows both mic and loudspeaker to cover the entire room along with flexibility of control and dialing using any conference phone



VENUES


Boardrooms

Medium Conference Rooms

Huddle Rooms

Home Office

Any Room Without Phone Lines



MAXAttach Wireless comes with two wireless phones that connect to a single base unit, providing expanded coverage in medium-sized rooms.

PRODUCT SPECIFICATIONS

Echo Cancellation

Tail time: 60 ms x 3

Noise Cancellation

Dynamic noise cancellation

Telephone Connection

Analog PBX or PSTN line

RJ-11C, -12 dBm nominal

Radio

Standard DECT/DECT 6.0 (NA, Canada, LATAM)

WDCT (EMEA, APAC)

ETSI EN 300 175 1-9

Keypad

Alphanumeric standard keypad

Loudspeaker

Volume: 90 dBspl A weighted @ 1 ft

Bandwidth: 200 Hz–3.3 kHz

Record Output

Connector: 2.5 mm mono audio jack

Impedance: <1000 ohms

Bandwidth: 200 Hz–3.3 kHz

Dynamic range: 60 dB

THD <.01%

Certifications

FCC part 15/ICES-003 Class A

FCC part 15 Subpart C/RSS-210

FCC part 68/IC CS-03

CE

UL Certified

Power

Phone Unit:

Custom battery pack with nickel metal hydride batteries, 7.2 V 2200 mAh

12 hours continuous talk time (typical)

36 hours standby

Base Unit:

Auto-adjusting power module;

100-240 VAC; 50/60Hz

Wireless Range

DECT: 300 ft to 400 ft (91-121 m)

EU WDCT unit: 50 ft (15 m)

Note: These ranges depend on environmental factors and may vary. The EU unit has a shorter range due to regulatory restrictions on power output in the 2.4 GHz frequency band in the EU.

Environmental

Operating temperature: 32–118° F (0–48° C)

Storage temperature: 41–158° F (5–70° C)

Operating humidity: 15 to 80%

Storage humidity: 10 to 90%

Dimensions (W x D x H)

Phone unit: 10.5" x 10.5" x 3"
(26.7 cm x 26.7 cm x 7.6 cm)

Base unit: 4.25" x 5.5" x 2.5"
(10.8 cm x 14 cm x 6.4 cm)

Weight

Phone unit: 2.7 lb (1.2 kg)

Base unit: .6 lb (0.27 kg)

Shipping: MAX Wireless: 10 lb (4.5 kg)

MAXAttach Wireless Includes

Wireless phone unit (2)

Base unit (1)

Battery pack (2)

Power supply/charger (2)

Power supply retainer (2)

Telephone cable

Documentation CD

Quick start guide

Part Numbers

MAXAttach

910-158-500-00 (MAXAttach)

910-158-500-01 (MAXAttach plus one)

910-158-500-02 (MAXAttach plus two)

MAXAttach Wireless

910-158-600-00 (MAXAttach Wireless DECT)

SALES AND INQUIRIES

Headquarters

5225 Wiley Post Way
Suite 500
Salt Lake City, UT 84116

US & Canada

Tel: 801.975.7200
TollFree: 800.945.7730
Fax: 801.303.5711

International

Tel: +1.801.975.7200
global@clearone.com

Sales

Tel: 801.975.7200
sales@clearone.com

TechSales

Tel: 801.974.3760
techsales@clearone.com

TechSupport

Tel: 801.974.3760
tech.support@clearone.com